

Holkoi Interactive Touch Panels

Model HOLKOI-01N LED

Key to Smart Class
Education



FEATURES

- 65" or 75" or 86" ED Interactive Panel sizes
- 20 points touch
- 4K UHD resolution
- Panel OS: Android 12.0, 4G RAM, 32G ROM
- OPS : i3/i5, 8G, 256G or higher, Pre-install Win10



HOLKOI

+91 7499345702
www.holkoigroup.com

Product Introduction

HOLKOI-01N LED Interactive Touch Panel is an intelligent writing panel With a triple-sided ultra-narrow bezel design, sliding door lock protection and 4K UHD display, it's equipped with interactive whiteboards and wireless screen casting software in a man-machine Interaction way, enabling an interactive mode with multiple users and inter-connectivity, enriching presentation and enhancing the communication atmosphere.

Specifications:

Panel Parameters

- LED Panel Size 65",75" and 86" or (1655 mm, 1906 mm, 2185 mm)
- Backlight Type LED (DLED)
- Resolution(H×V) 3840×2160 (UHD)
- Color 10 bit 1.07B
- Brightness 550cd/m2
- Contrast 4000:1 (according to panel brand)
- Viewing angle 178°
- Display protection 4 mm tempered explosion-proof glass
- Backlight lifetime 50000 hours
- Speakers 15W*2 / 8Ω

System Parameters

Operating System Android System Android 12.0

CPU (Processor) Quad Core 1.5GHz

Storage RAM 4G; ROM 32GB (8G RAM : 128G ROM Optional)

Network LAN/ WiFi 2.4G +5G

Windows System (OPS) CPU i5 or i3 or i7 optional)

Storage Memory: 8G (4G/16G optional) ; Hard Disk: 256G SSD (512G/1TB optional)

Network LAN/ WiFi

OS Pre-install Windows 10 Pro

HOLKOI

+91 7499345702

www.holkoigroup.com

Camera and Microphone Parameters (Optional)

Camera Pixel: 43.0 M

Video resolution: 3840*2160

Lens: Fixed focal length lens, effective focal length 4.11mm

Drive: Free drive

Microphone Microphone type: Digital array microphone

Number of digital marks: 6

Pickup distance: 10 m

Drive: Windows 10 free drive

Echo cancellation: Supported

Touch Parameters

Touch technology IR touch; 20 points; HIB Free drive

Response speed ≤ 8 ms

Operation system Support Windows7/10, Android, Mac OS, Linux

Working temperature 0°C~60°C

Operating Voltage DC5V

Power consumption ≥ 0.5 W

Electrical Performance

Max Power ≤ 250 W ≤ 300 W ≤ 400 W

Standby power ≤ 0.5 W

Voltage 110-240V(AC) 50/60Hz

Connection Parameters and Accessories

Input ports AV*1, YPbPR*1, VGA*1, AUDIO*1, HDMI*3(Front*1), LAN(RJ45) *1

Output Ports SPDIF*1, Earphone*1

Other Ports USB2.0*2, USB3.0*3 (front*3) , RS232*1, Touch USB*2(front*1)

Function buttons 7 buttons in front bottom frame: Power, Source, Volume+/-, Home,

Accessories Power cable*1; Remote Control*1; Touch Pen*1; Instruction manual*1;

Warranty card*1; Wall brackets*1 set

Product Dimension

Items / Model No. 01N-65LED 01N-75LED 01N-86 LED

Panel Size 65" 75" 86"

Product dimension 1490*906*95mm 1710*1030*95mm 1957*1170*95mm

Packing dimension 1620*1054*200mm 1845*1190*200mm 2110*1375*200mm

Wall mount VESA 500*400mm 600*400mm 750*400mm

Weight 41kg/52kg 56 kg/67 kg 71 kg/82 kg

HOLKOI

+91 7499345702

www.holkoigroup.com

Smart Class Solutions



Holkoi has been designing and developing LED Projectors, Interactive panels , Smart Class and Home Cinema solutions. Over the, years our dedicated team of engineers have designed and customized unique home cinema and smart classes products. We are BIS, CE, ROHS, TM, ISO certified

LED PROJECTORS

Holkoi offers wide range of smart LED Projectors for class rooms and Corporate.

WHITE DIGITAL BOARDS

Holkoi Interactive White boards are designed with ceramic board and 20 touch IR and Optical sensors

EDU. SOFTWARE

Holkoi offers Educational software which can be used with Interactive panels or white boards



+91 7499345702

Holkoi Systems Pvt. Ltd.
586, 19th A Cross, 7th Main, BTM
Layout Stage 2, Bangalore 560076
info@holkoi.com

